

# ES 112 Second Midterm Examination

-A-

Fall 2003-2004

## 1 Recursive Function

(30 Points)

The function  $f(n)$ , where  $n$  is a nonnegative integer, is defined to as:

$$\begin{aligned}f(0) &= 2 \\f(1) &= 5 \\f(n) &= 2f(n-1) - f(n-2), \quad n \geq 2\end{aligned}$$

Write a C function that takes the number  $n$  as its argument, and calculates and returns  $f(n)$  as an integer. If  $n < 0$ , the function should return -1. The prototype is:

```
int f(int n);
```

## 2 A String Function

(35 Points)

Implement the following (standard C string library) function:

```
char *strcat(char *dest, const char *src);
```

The `strcat()` function appends the `src` string to the `dest` string overwriting the '`\0`' character at the end of `dest`, and then adds a terminating '`\0`' character. The function returns a pointer to the resulting string `dest`.

## 3 The Harmonic Mean

(35 Points)

The harmonic mean of  $n$  numbers  $x_1, x_2, \dots, x_n, H$ , is defined by the following equation:

$$\frac{1}{H} = \frac{1}{n} \cdot \left( \frac{1}{x_1} + \frac{1}{x_2} + \dots + \frac{1}{x_n} \right)$$

Write a function that takes two arguments: a pointer to the beginning of an array of doubles, and the number of elements in the array; and returns the harmonic mean of the numbers in the array. You may assume that all numbers in the array are non-zero. The prototype of the function should be:

```
double harmonicMean (double *numbers, int n);
```